Surface Mount Transient Voltage Suppressor Diode

Features


- ✧ Bi-directional ESD protection of one line
- ✧ Solid-state silicon-avalanche technology
- ✧ Working Voltage: 36.0V
- ✧ Peak Power up to 440 Watts @ 8 x 20μs Pulse
- ✧ Low Leakage current
- ✧ IEC 61000-4-2 (ESD) ±25kV (air), ±25kV (contact)
- ✧ IEC 61000-4-4 (EFT) 40A (5/50ns)

Applications

- ✧ Control & Monitoring Systems
- ✧ Portable Electronics
- ✧ Digital Sensor I/O Ports
- ✧ 36 Volt DC Protection

Mechanical Data

- ✧ UL Flame Rating : UL94V-0
- ✧ Reel Size : 7 inch
- ✧ RoHS/WEEE Compliant



Circuit Diagram



SOD323

Absolute Maximum Rating at T_A = 25 °C, unless otherwise specified

Rating	Symbol	Value	Units
Peak Pulse Power (t_p =8/20μs)	P_{PP}	440	Watts
Peak Pulse Current (t_p =8/20μs) (note1)	I_{pp}	8	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	±25 ±25	kV
Lead Soldering Temperature	T_L	260(10seconds)	℃
Junction Temperature	T_J	-55 to + 125	℃
Storage Temperature	T_{stg}	-55 to + 150	℃

OVREG Semiconductor (xi'an) Co.,Ltd.


Electrical Characteristics at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Min.	Typical	Max.	Units
Reverse Stand-Off Voltage	V_{RWM}				36.0	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	40			V
Reverse Leakage Current	I_R	V_{RWM}=36.0V, T=25℃			1	μA
Peak Pulse Current	I_{PP}	tp =8/20μs			8	A
Clamping Voltage	V_C	I_{PP}=1A, tp=8/20μs		42		V
Clamping Voltage	V_C	I_{PP}=8A, tp=8/20μs		55		V
Junction Capacitance	C_J	V_R = 0V, f = 1MHz		20	30	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. All parameters specified at T_A = 25°C unless otherwise noted.
2. These parameters are guaranteed by design and characterization.
3. Standard IEC 61000−4−2 with $C_{Discharge}$ = 150 pF, $R_{Discharge}$ = 330 Ω


Electrical Parameters at T_A = 25 °C, unless otherwise specified




OVREG Semiconductor (xi'an) Co.,Ltd.

Typical Characteristics at T_A = 25 °C, unless otherwise specified


Peak Pulse Power vs. Pulse Time




Power derating vs. Ambient temperature




Forward Clamping Voltage vs. peak PulseCurrent




Reverse Clamping Voltage vs. Peak Pulse Current



8/20uS Pulse Waveform





IEC61000-4-2 +8kV Pulse Waveform




OVREG Semiconductor (xi'an) Co.,Ltd.

Package information








COMMOM DIMENSION (MM)			
PKG	SOD323		
Symbol	MIN.	NOM.	MAX.
A	0.800	0.900	1.000
A1	0.000	0.050	0.100
A2	0.800	0.850	0.900
b	0.250	0.300	0.350
c	0.080	-	0.150
D	1.200	1.300	1.400
E	1.600	1.700	1.800
E1	2.500	2.600	2.700
L	0.475 REF		
L1	0.250	0.260	0.270
Q	0.250 REF		

Recommend PCB Layout



Notes: This PCB Layout Is For Reference Purposes Only

Marking



Ordering Information

Part number	Material	Type	Reel size	MOQ	MOQ/internal box	MOQ/carton
OVE3172K1	GREEN	T/R	7 inch	3k/reel	10reel= 30k/box	4boxes=120k/carton

OVREG Semiconductor (Xi'an) Co.,Ltd.