Surface Mount Transient Voltage Suppressor Diode

Features


- ✧ Uni-directional ESD protection for two lines
- ✧ Solid-state silicon-avalanche technology
- ✧ Working Voltage: 24V
- ✧ Peak Power up to 360 Watts @ 8 x 20μs Pulse
- ✧ Low Leakage current
- ✧ IEC 61000-4-2 (ESD) ±30kV (air), ±30kV (contact)

Applications

- ✧ Industrial control networks
- ✧ Smart distribution systems
- ✧ DeviceNet
- ✧ Factory automation systems

Mechanical Data

- ✧ UL Flame Rating : UL94V-0
- ✧ Reel Size : 7 inch
- ✧ RoHS/WEEE Complian



Circuit Diagram



SOT23

OVREG Semiconductor (xi'an) Co.Ltd.

Absolute Maximum Rating at T_A = 25 °C, unless otherwise specified

Rating	Symbol	Value	Units
Peak Pulse Power (t_p =8/20μs)	P_{PP}	360	Watts
Peak Pulse Current (t_p =8/20μs) (note1)	I_{pp}	8	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	±30 ±30	kV
Lead Soldering Temperature	T_L	260(10seconds)	℃
Junction Temperature	T_J	-55 to + 125	℃
Storage Temperature	T_{stg}	-55 to + 150	℃


Electrical Characteristics at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Min.	Typical	Max.	Units
Reverse Stand-Off Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	I_T=1mA	26.0			V
Reverse Leakage Current	I_R	V_{RWM}=24V, T=25℃			1	μA
Peak Pulse Current	I_{PP}	tp =8/20μs			8	A
Clamping Voltage	V_C	I_{PP}=1A, tp=8/20μs		27		V
Clamping Voltage	V_C	I_{PP}=8A, tp=8/20μs		40	45	V
Junction Capacitance	C_J	V_R = 0V, f = 1MHz		45	60	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. All parameters specified at T_A = 25°C unless otherwise noted.
2. These parameters are guaranteed by design and characterization.
3. Standard IEC 61000−4−2 with $C_{Discharge}$ = 150 pF, $R_{Discharge}$ = 330 Ω


Electrical Parameters at T_A = 25 °C, unless otherwise specified




OVREG Semiconductor (xi'an) Co.,Ltd.

Typical Characteristics at T_A = 25 °C, unless otherwise specified


8/20uS Pulse Waveform




Peak Pulse Power vs. Pulse Time




Capacitance vs. Reverse Voltage



Reverse Clamping Voltage vs. Peak Pulse Current




IEC61000-4-5 : 8/20us Waveform




OVREG Semiconductor (Xi'an) Co.,Ltd.

Package information




COMMON DIMENSION (MM)			
PKG	SOT23		
REF.	MIN.	NOM.	MAX.
A	0.90	-	1.15
A1	0.00	-	0.10
A2	0.90	1.00	1.05
b	0.30	-	0.50
c	0.08	-	0.15
D	2.80	2.90	3.00
E	1.20	1.30	1.40
E1	2.25	2.40	2.55
e	0.95TYP		
e1	1.80	1.90	2.00
L	0.55REF		
L1	0.30	0.45	0.50

Recommend PCB Layout



Notes: This PCB Layout Is For Reference Purposes Only

Marking



Ordering Information

Part number	Material	Type	Reel size	MOQ	MOQ/internal box	MOQ/carton
OVE6125M1	GREEN	T/R	7 inch	3k/reel	10reel= 30k/box	4boxes=120k/carton

OVREG Semiconductor (xi'an) Co.,Ltd.