

400W Surface Mount Transient Voltage Suppressor

Features


- ✧ 400W Peak Pulse power capability at 10/1000us waveform
- ✧ Unidirectional and Bidirectional Protection
- ✧ High temperature soldering: 260°C/10s at terminals
- ✧ Fast response time
- ✧ Glass passivated junction
- ✧ Low profile package

Applications

- ✧ I/O interfaces, VCC bus
- ✧ Power lines
- ✧ Automotive and Telecommunication
- ✧ Industrial Electronics
- ✧ Computers & Consumer Electronics

Mechanical Data

- ✧ UL Flame Rating : UL94V-0
- ✧ RoHS/WEEE Compliant



DO-214AC

Absolute Maximum Rating at $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified


Rating	Symbol	Value	Units
Peak Pulse Power ($t_p = 10/1000\mu\text{s}$)	P_{PPM}	400	W
Peak Pulse Current ($t_p = 10/1000\mu\text{s}$)	I_{pp}	See next table	A
Power Dissipation on Infinite Heat Sink at $T_L = 50^{\circ}\text{C}$	P_D	3.3	W
Peak Forward Surge Current, 8.3ms Single Half Sine Wave	I_{FSM}	40	A
Operating Temperature	T_J	-55 to + 150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to + 150	$^{\circ}\text{C}$

Electrical Characteristics at $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified


Part Number		Marking		V_R	$I_{R@V_R}$	$V_{BR@I_T}$		I_T	$V_C@I_{PP}$	I_{PP}
Uni-Polar	Bi-Polar	UNI	BI	V	μA	min(V)	max(V)	mA	max(V)	A
SMAJ5.0A	SMAJ5.0CA	AE	WE	5.0	800	6.40	7.07	10	9.2	43.5
SMAJ6.0A	SMAJ6.0CA	AG	WG	6.0	800	6.67	7.37	10	10.3	38.8
SMAJ6.5A	SMAJ6.5CA	AK	WK	6.5	500	7.22	7.98	10	11.2	35.7
SMAJ7.0A	SMAJ7.0CA	AM	WM	7.0	200	7.78	8.60	10	12.0	33.3
SMAJ7.5A	SMAJ7.5CA	AP	WP	7.5	100	8.33	9.21	1	12.9	31.0
SMAJ8.0A	SMAJ8.0CA	AR	WR	8.0	50	8.89	9.83	1	13.6	29.4
SMAJ8.5A	SMAJ8.5CA	AT	WT	8.5	20	9.44	10.40	1	14.4	27.8
SMAJ9.0A	SMAJ9.0CA	AV	WV	9.0	10	10.00	11.10	1	15.4	26.0
SMAJ10A	SMAJ10CA	AX	WX	10	5	11.10	12.30	1	17.0	23.5
SMAJ11A	SMAJ11CA	AZ	WZ	11	5	12.20	13.50	1	18.2	22.0
SMAJ12A	SMAJ12CA	BE	XE	12	5	13.30	14.70	1	19.9	20.1
SMAJ13A	SMAJ13CA	BG	XG	13	1	14.40	15.90	1	21.5	18.6
SMAJ14A	SMAJ14CA	BK	XK	14	1	15.60	17.20	1	23.2	17.2
SMAJ15A	SMAJ15CA	DM	BM	15	1	16.70	18.50	1	24.4	16.4
SMAJ16A	SMAJ16CA	BP	XP	16	1	17.80	19.70	1	26.0	15.4
SMAJ17A	SMAJ17CA	BR	XR	17	1	18.90	20.90	1	27.6	14.5
SMAJ18A	SMAJ18CA	BT	XT	18	1	20.00	22.10	1	29.2	13.7
SMAJ20A	SMAJ20CA	BV	XV	20	1	22.20	24.50	1	32.4	12.3
SMAJ22A	SMAJ22CA	BX	XX	22	1	24.40	26.90	1	35.5	11.3
SMAJ24A	SMAJ24CA	BZ	XZ	24	1	26.70	29.50	1	38.9	10.3
SMAJ26A	SMAJ26CA	CE	YE	26	1	28.90	31.90	1	42.1	9.5
SMAJ28A	SMAJ28CA	CG	YG	28	1	31.10	34.40	1	45.4	8.8
SMAJ30A	SMAJ30CA	CK	YK	30	1	33.30	36.80	1	48.4	8.3
SMAJ33A	SMAJ33CA	CM	YM	33	1	36.70	40.60	1	53.3	7.5
SMAJ36A	SMAJ36CA	CP	YP	36	1	40.00	44.20	1	58.1	6.9
SMAJ40A	SMAJ40CA	CR	YR	40	1	44.40	49.10	1	64.5	6.2
SMAJ43A	SMAJ43CA	CT	YT	43	1	47.80	52.80	1	69.4	5.8
SMAJ45A	SMAJ45CA	CV	YV	45	1	50.00	55.30	1	72.7	5.5
SMAJ48A	SMAJ48CA	CX	YX	48	1	53.30	58.90	1	77.4	5.2
SMAJ51A	SMAJ51CA	CZ	YZ	51	1	56.70	62.70	1	82.4	4.9
SMAJ54A	SMAJ54CA	RE	ZE	54	1	60.00	66.30	1	87.1	4.6
SMAJ58A	SMAJ58CA	RG	ZG	58	1	64.40	71.20	1	93.6	4.3
SMAJ60A	SMAJ60CA	RK	ZK	60	1	66.70	73.70	1	96.8	4.1
SMAJ64A	SMAJ64CA	RM	ZM	64	1	71.10	78.60	1	103.0	3.9
SMAJ70A	SMAJ70CA	RP	ZP	70	1	77.80	86.00	1	113.0	3.5
SMAJ75A	SMAJ75CA	RR	ZR	75	1	83.30	92.10	1	121.0	3.3
SMAJ78A	SMAJ78CA	RT	ZT	78	1	86.70	95.80	1	126.0	3.2
SMAJ85A	SMAJ85CA	RV	ZV	85	1	94.40	104.0	1	137.0	2.9
SMAJ90A	SMAJ90CA	RX	ZX	90	1	100.0	111.0	1	146.0	2.7
SMAJ100A	SMAJ100CA	RZ	ZZ	100	1	111.0	123.0	1	162.0	2.5
SMAJ110A	SMAJ110CA	SE	VE	110	1	122.0	135.0	1	177.0	2.3
SMAJ120A	SMAJ120CA	SG	VG	120	1	133.0	147.0	1	193.0	2.0
SMAJ130A	SMAJ130CA	SK	VK	130	1	144.0	159.0	1	209.0	1.9
SMAJ150A	SMAJ150CA	SM	VM	150	1	167.0	185.0	1	243.0	1.6
SMAJ160A	SMAJ160CA	SP	VP	160	1	178.0	197.0	1	259.0	1.5
SMAJ170A	SMAJ170CA	SR	VR	170	1	189.0	209.0	1	275.0	1.4
SMAJ180A	SMAJ180CA	ST	VT	180	1	201.0	222.0	1	292.0	1.4
SMAJ200A	SMAJ200CA	SV	VV	200	1	224.0	247.0	1	324.0	1.2
SMAJ220A	SMAJ220CA	SX	VX	220	1	246.0	282.0	1	356.0	1.1
SMAJ250A	SMAJ250CA	SZ	VZ	250	1	279.0	309.0	1	405.0	1.0
SMAJ300A	SMAJ300CA	TE	UE	300	1	335.0	371.0	1	486.0	0.8
SMAJ350A	SMAJ350CA	TG	UG	350	1	391.0	432.0	1	567.0	0.7
SMAJ400A	SMAJ400CA	TK	UK	400	1	447.0	492.0	1	648.0	0.6
SMAJ440A	SMAJ440CA	TM	UM	440	1	492.0	543.0	1	713.0	0.6

Typical Characteristics at $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified


Non-repetitive Peak Pulse Power vs. Pulse Time




Power derating vs. Ambient temperature




Pulse Waveform



Capacitance vs. Reverse Voltage




Soldering Parameters




Reflow Condition		Pb – Free assembly
Pre Heat	- Temperature Min ($T_{S(min)}$)	150°C
	- Temperature Max ($T_{S(max)}$)	200°C
	- Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus) Temp(T_L) to peak		3°C/second max
$T_{S(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	- Temperature (T_L) (Liquidus)	220°C
	- Temperature (t_L)	60 – 150 seconds
Peak Temp(T_P)		260 $\pm$ 0/-5 °C
Time within 5°C of actual peak Temperature (t_P)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		260°C

Package Information




Recommend PCB Layout



Notes: This PCB Layout Is For Reference Purposes Only

Marking



Ordering Information

Part number	Package	Type	Reel size	MOQ	Packaging specification
SMAJxxx(C)A	DO-214AC	T/R	11 inch	5k/reel	EIA STD RS-481