

Dual Series Schottky Barrier Diode

Description


These Schottky barrier diodes are optimized for low forward voltage drop and low leakage current that offers the most optimal power dissipation in applications. They are housed in spacing saving micro-packaging ideal for space constraint applications.

Features

- ✧ Low Forward Voltage Drop: 500 mV (Max.) @ $I_F = 30$ mA
- ✧ Low Reverse Current: 2 μ A (Max.) @ $V_R = 25$ V
- ✧ 200 mA of Continuous Forward Current
- ✧ High Switching Speed
- ✧ Pb-Free, Halogen Free/BFR Free and RoHS Compliant

Applications

- ✧ Low current rectification
- ✧ Camera Photo Flash
- ✧ Buck and Boost dc-dc Converters
- ✧ Voltage and Current Protection



Circuit Diagram



SOT323


Absolute Maximum Rating ($T_A = 25$ °C, unless otherwise specified)

Rating	Symbol	Value	Units
Reverse Voltage (DC)	V_R	30	V
Forward Current (DC)	I_F	200	mA
Forward Surge Current (60 Hz @ 1 cycle)	I_{FSM}	600	mA
Junction temperature	T_j	125	°C
Storage temperature	T_{stg}	-55~+150	°C




Electrical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typical	Max.	Units
Reverse Leakage	I_R	$V_R=25\text{V}$	-	-	2	μA
Forward Voltage	V_F	$I_F=1\text{mA}$ $I_F=10\text{mA}$ $I_F=30\text{mA}$ $I_F=100\text{mA}$	-	-	0.32 0.40 0.50 1.00	V
Total Capacitance	C_T	$V_R = 1\text{V}$, $f = 1\text{MHz}$	-	-	10	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mAdc}$ $I_{R(\text{REC})} = 1.0\text{ mAdc}$	--		5.0	ns


Electrical Parameters ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)



Typical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Package Information



SOT323			
DIM	MIN	NOR	MAX
A	0.80	0.95	1.00
A1	0.00	0.05	0.10
A2	0.7 REF		
b	0.30	0.35	0.40
c	0.10	0.15	0.25
D	1.80	2.05	2.20
E	1.15	1.30	1.35
e	1.20	1.30	1.40
e1	0.65 BSC		
L	0.20	0.35	0.56
He	2.00	2.10	2.40
ALL Dimension in mm			


Recommend PCB Layout



DIM	MIN
A	1.90
B	0.65
C	0.65
X	0.70
Y	0.90

Notes: This Pcb Layout Is For Reference Purposes Only

Marking



Ordering Information

Part number	Material	Type	Reel size	MOQ	MOQ/internal box	MOQ/carton
OVB12TL37R	GREEN	T/R	7 inch	3k/reel	10reel= 30k/box	4boxes=120k/carton