


Schottky Barrier Diode

Description

These Schottky barrier diodes are optimized for low forward voltage drop and low leakage current that offers the most optimal power dissipation in applications. They are housed in spacing saving micro-packaging ideal for space constraint applications.

Features

- ✧ Low Forward Voltage Drop
- ✧ Surface Mount device
- ✧ 1 A of Continuous Forward Current
- ✧ High Response Speed
- ✧ Halogen Free and RoHS Compliant



Circuit Diagram

Applications

- ✧ Low Voltage Rectification
- ✧ Switch Mode Power Supply
- ✧ Dc-Dc Converters
- ✧ Reverse Voltage and Current Protection



SOD323


Absolute Maximum Rating ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Rating	Symbol	Value	Units
Reverse Voltage (DC)	V_R	40	V
Forward Current (DC)	I_F	1	A
Forward Surge Current (60Hz @ 1 cycle)	I_{FSM}	9	A
Junction temperature	T_j	125	$^{\circ}\text{C}$
Storage temperature	T_{stg}	-50~+125	$^{\circ}\text{C}$





Electrical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typical	Max.	Units
Reverse Breakdown Voltage	V_{BR}	$I_R=1\text{mA}$	40			V
Reverse Leakage	I_R	$V_R=40\text{V}$			500	μA
Forward Voltage	V_F	$I_F=1.0\text{A}$ $I_F=3.0\text{A}$			0.60 0.90	V
Total Capacitance	C_T	$V_R = 10\text{V}$, $f = 1\text{MHz}$		110		pF



Electrical Parameters ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)



Typical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Package Information



Symbol	Dimensions In Millimeters	
	Min.	Max.
A	0.800	1.000
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.250	2.750
L	0.475 REF	
L1	0.250	0.400
θ	0°	8°

Recommend PCB Layout



Notes: This PCB Layout Is For Reference Purposes Only

Marking



X:DATE CODE

Ordering Information

Part number	Material	Type	Reel size	MOQ	MOQ/internal box	MOQ/carton
OVB72FK21A	GREEN	T/R	7 inch	3k/reel	10reel= 30k/box	4boxes=120k/carton